



SERIES

UH

UH 4800 Multi-Cut



W°

WILLIBALD

Technical specifications of the UH 4800



output



drive position



operating position



service position

Technical specifications: UH 4800

engine	MAN
power	353 kW / 480 HP
throughput	
- greenwaste	up to 220 m ³ /h
- wood waste	up to 130 m ³ /h
- pre-shredded wood waste	up to 210 m ³ /h
- bark	up to 230 m ³ /h
feed opening	
- width	1450 mm
- height	1000 mm
height of loading	2200 mm
height of transfer	4,0 m (optional 4,5 m)
fixed hammers	24 pcs
diameter of rotor	1000 mm
dimensions LxBxH	11000x2550x3950 mm
weight	up to 18000 kg

Options:

- hydr. feed-hopper extension
- magnetic separator
- hydr. support feet, controlled remotely
- hydr. tailgate raise
- sidewise loading conveyor
- mounting star screen
- additional fuel tank
- wheel drive
- reversable fan
- remote control
- crawler track type chassis
- central lubrication system
- hydr. axle extractor
- working lights

technical changes reserved
stand: 03/2009



WILLIBALD

J. Willibald GmbH Bahnhofstraße 6 D-88639 Wald-Sentenhart
Tel.: +49 (0) 7578 / 18 90 Fax: +49 (0) 7578 / 18 91 70
 e-mail: info@willibald-gmbh.de www.willibald-gmbh.de